

FUMAIR



**ADSORB
CLEANCHANGE
EDUCATION MODEL
MOBILE FUME CABINET**





CABINET SPECIFICATION

The Fumair Adsorb Cleanchange Education Model has been designed to provide full protection. It is constructed as an open-fronted safety enclosure with ductless filtration to provide fully filtered air from activated carbon filters (Type GRD).

Cabinet Dimensions: Width: 1000mm / 1200mm Depth: 750mm Height: 1971mm

Performance: Face Velocity: >0.3 metres per second
Changes of air: 7.5 metres per minute
Noise Level: 40dBa
Power Supply: 240 V single phase 50Hz
Power Consumption: 96 watts
Max amps adsorbed: 0.5 amps

Filtration: Pre-filter: F9 Electret Pad
Main Filter: Activated Carbon filter (Type GRD) in accordance with Building Bulletin 88. CLEAPPS tested.

OPTIONAL EXTRAS

Filter Alarm: Measures the pressure loss across the pre-filter only and will indicate when the filter has become blocked and requires changing.

Water Supply: Swan water spout, fitted on/off tap complete with flexible hose and quick release connectors. Drip cup is fitted with connecting drain hose

Gas Supply: Gas spout fitted with on/off tap completed with flexible hose and quick release connectors.

Power Supply: 13 amp twin RCD socket.

Internal Illumination: Two 35W MR16 Low Voltage Halogen light bulbs.

FUMAIR LTD
UNIT 21, MEAD BUSINESS CENTRE, MEAD LANE, HERTFORD
Tel: +44 (0)1992 589115 Fax: +44 (0)1992 584905 Email: sales@fumair.co.uk